

### Flexible and accurate positioning

Shigemitsu S Series turntable 360 degrees rotation, lifting arm can extend a maximum of 14.5 meters, the platform can be rotated 180 degrees, work location and perfect service, easily transferred across the barrier.

### Powerful extension capability

Shigemitsu series provide users with powerful extension capability, and its extended range can be up to 14.5 meters, providing convenience for a variety of environmental work.



| Model                  | TM1470C                         | TM1770C               | TM2110C       | TM2512C       | TM2815C       |
|------------------------|---------------------------------|-----------------------|---------------|---------------|---------------|
| Working Height (m)     | 14.35                           | 17.20                 | 20.00         | 24.80         | 27.80         |
| Platform Height (m)    | 12.35                           | 15.20                 | 18.00         | 22.80         | 25.80         |
| Outreach Max (m)       | 7.00                            | 7.40                  | 10.00         | 12.50         | 14.50         |
| Turntable Rotation°    | 360                             | 360                   | 360           | 360           | 360           |
| Lift Capacity (Kg)     | 200                             | 220                   | 220           | 220           | 220           |
| Platform Rotation°     | 180                             | 180                   | 180           | 180           | 180           |
| Platform Size (mm)     | 1500*800*1150                   | 1500*800*1150         | 1500*800*1150 | 1780*730*1120 | 1700*700*1100 |
| Height-Stowed (mm) (1) | 2700                            | 2400                  | 2400          | 3000          | 2920          |
| Length-Stowed (mm) (6) | 6350                            | 5790                  | 5790          | 8300          | 6900          |
| Width-Stowed (mm) (9)  | 2100                            | 2100                  | 2100          | 2550          | 2200          |
| Controls               | Electrical Proportional Control |                       |               |               |               |
| Outriggers Type        | Hydraulic                       |                       |               |               |               |
| Articulating Type      | Steel Single Quads Type         | Steel Dual Quads Type |               |               |               |
| Chassis Specification  | 2T                              | 3.5T                  | 3.5T          | 6T            | 6T            |

Detailed Parameters, Please Consult The Shigemitsu Salles Representatives

### TM Working Range

